Walsh





4200 SINGLE SLIDE						
WINDOW TYPE	GLASS Package	U-VALUE	SHCC	VISIBLE Transmittance	CONDENSATION Resistance	CLIMATE Zone Map
NO FOAM	#1	.29	.41	.58	.60	NC
FOAM	#1	.28	.41	.58	.60	NC
NO FOAM	#2	.28	.22	.52	.61	NC
FOAM	#2	.27	.22	.52	.61	N-NC
NO FOAM	#3	.24	.22	.51	.51	N-NC
FOAM	#3	.22	.22	.51	.51	N-NC
GLASS PACKAGE						
TYPE #1	CLEAR/ARGON/LOE 272			3/4" IG LOE SURFACE #3		
TYPE #2	LOE 366/ARGON/CLEAR			3/4" IG LOE SURFACE #2		
TYPE #3	LOE 366/	'ARGON/LOE-I	89	3/4" IG LOE SURFACE #2 AND #4		



Black

laminate exterior white interior

White

Single Slide Features

- · All welded frame and sash.
- Sloped sill designed for efficient water evacuation.
- Full complement of accessory profiles.
- 3¼" frame width ideal for replacement installations.
- Exterior glazed equal glass sash.
- Tandem rollers for enhanced operation.
- Frame options: Replacement frame, regular nail fin frame, J-fin designed with brick mold accent frame.
- Maximum glass thickness of ¾".
- Optimum designed aluminum sash reinforcement.
- · Dual weatherstripping.
- Multi chambered vinyl profiles for thermal efficiency.
- Up to DP50 performance levels.
- Interlocks designed for ease of operation and positive engagement.
- · Operating panel lifts out for cleaning

Almond